

# GeneRegionScan

March 24, 2012

---

ProbeLevelSet-class

*Class ProbeLevelSet*

---

## Description

This is the storage class for Probe Level data with attached probe annotation

## Class definition

The class is derived from class ExpressionSet in the Biobase package.

## Author(s)

Diego Diez

---

addSnpData

*Add SNP data from hapmap-style data file to pData of ExpressionSet*

---

## Description

Function that will add genotypes to an ExpressionSet when given a data file with genotypes in the same format as outputted by <http://www.hapmap.org>.

## Usage

```
addSnpData(object, listOfSnps, individualNames="sampleNames")
```

## Arguments

object	A ProbeLevelSet object or a regular ExpressionSet object (in which case a probeData argument is required). See <a href="#">getLocalProbeIntensities</a> and related functions on how to create a ProbeLevelSet.
listOfSnps	A character string giving the path of a file containing SNP data in the same format as used by the export function of <a href="http://www.hapmap.org">www.hapmap.org</a> .
individualNames	An optional character string giving the column name of a pData entry that holds the individual names as given in the listOfSnps. This defaults to using the sampleNames, and is useful in cases with replicate or triplicate samples

## Details

A function that takes an ExpressionSet and the path for a SNP-file. The SNP-file should have the same format as files downloaded from <http://www.hapmap.org>. The function then checks if the sampleNames are present in the SNP-file. If they are, it decorates the ExpressionSet with the SNPs. If the snp name already exists as a column name in the pData, the function tries to merge the new information from listOfSnps with the new. Original NA values are overwritten by new values. Original values that are the same as new values are kept the same. Original values that are not the same as new values are preserved in their original state and a warning is given.

## Value

The same ProbeLevelSet or ExpressionSet given as argument, but with the SNP type data added to the pData and with the extra information of the listOfSnps file added to the notes section.

## Author(s)

Lasse Folkersen

## See Also

[getLocalProbeIntensities](#), [plotOnGene](#)

## Examples

```
## Not run:
hapmapformatdata<-"~/somefile.txt"
probelevelsetwithsnps<-addSnpPdata (probelevelset, hapmapformatdata)

## End (Not run)
```

---

checkForFilePath *Check For File In Path*

---

## Description

Internal function used to check for files in path.

## Usage

```
checkForFilePath (filenames)
```

## Arguments

`filenames` A character vector of filenames to check for - c("xxxx.exe", "xxxx") for example

## Details

This function is not meant to be called by the user so it is not in the namespace.

## Value

A character vector with the expanded paths and filenames to the found files.

**Author(s)**

Lasse Folkersen

**See Also**[plotOnGene](#)**Examples**

```
GeneRegionScan:::checkForFileInPath(c("python", "python.exe"))
```

---

doProbeLinear	<i>Do Probe Linear</i>
---------------	------------------------

---

**Description**

Internal function used to calculate linear correlation between probe level intensity and factorial pData entries such as genotypes.

**Usage**

```
doProbeLinear(object, label, testType="linear model")
```

**Arguments**

object	A ProbeLevelSet object or a regular ExpressionSet object.
label	An optional character string specifying a column name in the pData of the object. If this argument is given, the gene plot will be colour coded based on the different groups (factors) in the pData entry. If a summaryType other than 'dots' is selected the summarisation is done stratified by the different groups in the pData.
testType	Character string, defining a statistic procedure to identify especially interesting probes.

**Details**

This function is not meant to be called by the user. It does the statistical calculations when called by [plotStatistics](#).

One important note about the assumption that the alphabetical order is the same as value order. This usually works with SNP datatypes of the type AA, AB, BB. However the sorting is locale dependent and can produce odd results, which is why the value assignments are always printed. See [Comparison](#) for details on this. Further user-control over this aspect of the plotting function was omitted, giving more weight to the simplicity of the function interface. In case of problems it is recommended to rename the entries in the label so that they will be correctly sorted.

**Value**

A correlation list with p-value and fold-change in columns and probe IDs as rownames. Used by [plotStatistics](#) when decorating plots from [plotOnGene](#).

**Author(s)**

Lasse Folkersen

**See Also**[plotStatistics](#), [plotOnGene](#)**Examples**

```

data(exampleProbeLevelSet)
colnames(pData(exampleProbeLevelSet))
linearModelData<-GeneRegionScan:::doProbeLinear(exampleProbeLevelSet,"genotype3")
colnames(linearModelData)
#P value for the probe with ID 679083 in relation to "genotype3"
print(linearModelData["679083","p-value"])

```

doProbeTTest

*Do Probe T-Test***Description**

Internal function used to calculate t-tests between probe level intensity and pData entries with two levels.

**Usage**

```
doProbeTTest(object, label, testType="students")
```

**Arguments**

object	A ProbeLevelSet object or a regular ExpressionSet object.
label	An optional character string specifying a column name in the pData of the object. If this argument is given, the gene plot will be colour coded based on the different groups (factors) in the pData entry. If a summaryType other than 'dots' is selected the summarisation is done stratified by the different groups in the pData.
testType	Character string, defining a statistic procedure to identify especially interesting probes.

**Details**

This function is not meant to be called by the user. It does the statistical calculations when called by [plotStatistics](#)

**Value**

A correlation list with p-value and fold-change in columns and probe IDs as rownames. Used by [plotStatistics](#) when decorating plots from [plotOnGene](#).

**Author(s)**

Lasse Folkersen

**See Also**[plotStatistics](#), [plotOnGene](#)**Examples**

```
data(exampleProbeLevelSet)
colnames(pData(exampleProbeLevelSet))
tTestData<-GeneRegionScan:::doProbeTTest(exampleProbeLevelSet,"gender")
colnames(tTestData)

#P value for the probe with ID 679083 in relation to "gender"
print(tTestData["679083","p-value"])
```

---

`exampleProbeLevelSet`*Example Dataset of class 'ProbeLevelSet'*

---

**Description**

This `ProbeLevelSet` is derived from Human exon ST 1.0 cel files downloaded from the <http://www.ncbi.nlm.nih.gov/geo/>. The `pData` in the `ProbeLevelSet` is entirely fictional, and the intensity have been changed for some probes to show a point about correlation to genotype.

**Usage**

```
data(exampleProbeLevelSet)
```

**Format**

A `ProbeLevelSet` object containing probe level intensity data for a region on chromosome 2.

**Author(s)**

Lasse Folkersen

**Examples**

```
data(exampleProbeLevelSet)
pData(exampleProbeLevelSet)
exprs(exampleProbeLevelSet)[1:10,]
```

---

```
excludeDoubleMatchingProbes
```

*Exclude ProbeLevelSet probes that match more than once in genome*

---

### Description

Function that will remove probes from ProbeLevelSet if they have more than one match in a given genome.

### Usage

```
excludeDoubleMatchingProbes(object, genome="BSgenome.Hsapiens.UCSC.hg18", verbose=TRUE,
directions=c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense"),
previousData = NULL)
```

### Arguments

<code>object</code>	A ProbeLevelSet class object.
<code>genome</code>	character string with the name of the BSgenome in which sequences should be found. Defaults to the human genome.
<code>verbose</code>	TRUE or FALSE.
<code>directions</code>	character string with elements from <code>c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense")</code> . Defines which directions (complementary and reverse mirrorings) that should be scanned. Defaults to all directions.
<code>previousData</code>	Optional: The output from a call to <code>findSequenceInGenome</code> . If given the scanning will be skipped, and the probes will be omitted directly. Useful in cases where datasets from the same region needs to be processed.

### Details

This function will take quite a while to run, so if you have many sequences, overnight runs are recommended. BSgenome contains some alternative versions of chromosomes. They are marked with an underscore. This function automatically disregards chromosome names with an underscore, and this is known to work for the human genome. Nevertheless, check the output printed to terminal if all chromosomes are included. The function is a wrapper around `findSequenceInGenome`, which can be used for purposes that are more flexible (although that function really is just following the example in the BSgenome package)

At present, there is no functionality to check matches with known SNP or known splice forms taken into account.

### Value

The ProbeLevelSet class object provided as argument, with all double matching probes removed. Double matching probes are probes whose sequence are found twice or more in the genome. In addition, the output of the matching investigation is saved in the notes of the ProbeLevelSet and can be further examined for information on the locations of the probe sequences in relation to the BSgenome sequences.

**Author(s)**

Lasse Folkersen

**See Also**[findSequenceInGenome](#), [BSgenome](#), [excludeDoubleMatchingProbes](#)**Examples**

```
## Not run:
#you can run this, but it takes a lot of time
probelevelsetwithnodoubles<-excludeDoubleMatchingProbes (probelevelset)

## End (Not run)
```

---

exonStructure      *Add exon-structure to plots*

---

**Description**

Function that will paint the exon structure of a gene on the plots obtained by `plotOnGene`.

**Usage**

```
exonStructure(mrna, genome, maxMismatch=4, y=0)
```

**Arguments**

<code>mrna</code>	A gene sequence formatted as <code>DNAstring</code> , character-vectors or <a href="#">readFASTA</a> output.
<code>genome</code>	A number of gene sequences as <code>DNAstring</code> , vectors of <code>DNAStrings</code> , character-vectors or <a href="#">readFASTA</a> outputs.
<code>maxMismatch</code>	Integer. The maximum number of mismatches per exon that can be allowed before the exon is not allocated at the position in the template mrna. Defaults to 4.
<code>y</code>	Numeric. The vertical position of the exon structure (if <code>ylim</code> is changed)

**Details**

When given a sequence of the DNA divided by exons and a sequence of the corresponding mRNA string, this function will plot the layout of exons along the length of the x-axis on the current device. The sequences have to be given as FASTA sequences produced by the [readFASTA](#) function in the `Biostrings` package. Furthermore the genome must be divided with an entry for each exon. This is easily done by downloading the genome sequences of the gene-of-interest from <http://genome.ucsc.edu> and specifying "One FASTA record per region".

The function works by sequentially comparing each exon to the mrna. The location of the match start and end is taken as the exon boundaries and plotted. If more than one match is found a warning is given. If no match is found for an exon this is printed, but otherwise ignored. The mrna can in fact also be DNA sequence with introns. The important thing is that it serves as template for the exon matching.

Importantly, the exon-numbers technically refer to "number of exon in investigated transcript". For example if an DNA with exon structure for an isoform which does not include all exons in the gene is investigated, then there will be skips of exon numbers. To avoid this, the DNA for an isoform which do include all exons could be used. However, it is really more a biological issue: different sources can differ on where to start the counting for a given gene in any case.

### Value

No value, but plots the layout of exons in a gene on the product of a call to [plotOnGene](#).

### Author(s)

Lasse Folkersen

### See Also

[geneRegionScan](#), [plotOnGene](#)

### Examples

```
data(exampleProbeLevelSet)
plotOnGene(exampleProbeLevelSet, mrna, label="gender", testType="wilcoxon")
exonStructure(mrna, genomic, maxMismatch=2)
```

---

findProbePositions *Find positions of probes on a gene*

---

### Description

Function that will the location of probes in a gene based on their sequence.

### Usage

```
findProbePositions(object, gene, probeData=NULL, interval=NULL, directions="all")
```

### Arguments

object	A ProbeLevelSet object or a regular ExpressionSet object (in which case a probeData argument is required). See <a href="#">getLocalProbeIntensities</a> and related functions on how to create a ProbeLevelSet.
gene	A number of gene sequences as DNASTring, vectors of DNASTrings, character-vectors or <a href="#">readFASTA</a> outputs.
probeData	Optional if a ProbeLevelSet is submitted as object argument. Otherwise, it must be a data frame with rownames corresponding to the featureNames of the ExpressionSet and a column named "sequence" with the probe sequences as character strings
interval	Optional vector of two integers of bp positions. If given, the plot will only include the sequence from gene in the given interval. The x-axis annotation is preserved from original, so this is useful for zooming on specific regions.
verbose	TRUE or FALSE



`directions` A character vector of the matching-directions that should be scanned (which combinations of complementary and reverse). Defaults to "all" which is shorthand for all possible directions, but can take anything from: `c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense")`

### Details

This function is principally used by the `plotOnGene` to assign positions of each probe relative to the gene sequence of interest. In a recent version of `GeneRegionScan` it was separated as a discrete function because of its use in alternative plotting

### Value

A vector of positions of each probe in the object `ProbeLevelSet`, with names being probe ids

### Author(s)

Lasse Folkersen

### See Also

[geneRegionScan](#), [plotOnGene](#), [plotCoexpression](#)

### Examples

```
data(exampleProbeLevelSet)
findProbePositions(exampleProbeLevelSet, mrna)
```

---

`findSequenceInGenome`

*Find a sequence in genome*

---

### Description

Wrapper around `matchPDict` that will accept a list of sequences and check if they are present in a given genome. Takes a long time to run.

### Usage

```
findSequenceInGenome(sequences,
  genome="BSgenome.Hsapiens.UCSC.hg19", verbose=TRUE,
  directions=c("matchForwardSense", "matchForwardAntisense",
    "matchReverseSense", "matchReverseAntisense"))
```

**Arguments**

<code>sequences</code>	vector of character strings to scan. Should only contain A, C, G and T. Will be converted to DNAStrng.
<code>genome</code>	character string with the name of the BSGenome in which sequences should be found. Defaults to the human genome.
<code>verbose</code>	TRUE or FALSE.
<code>directions</code>	character string with elements from <code>c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense")</code> . Defines which directions (complementary and reverse mirrorings) that should be scanned. Defaults to all directions.

**Details**

This function will take quite a while to run, so if you have a many sequences, overnight runs are recommended. BSGenome contains some alternative versions of chromosomes. They are marked with an underscore. This function automatically disregards chromosome names with an underscore, and this is known to work for the human genome. Nevertheless, check the output printed to terminal if all chromosomes are included.

**Value**

A data frame with a row for each identified match. Columns are "entrynumber", "hitposInChr", "chr", and "sequence" describing, respectively: the index of the sequence match, the position in the chromosome at which it was found, which chromosome it was found on, the sequence itself

**Author(s)**

Lasse Folkersen

**See Also**

[BSgenome](#), [matchPDict](#), [excludeDoubleMatchingProbes](#)

**Examples**

```
## Not run:
#you can run this, but it takes quite a lot of time
example<-findSequenceInGenome("CTGGCGAGCAGCGAATAATGGTTT")

## End(Not run)
```

---

geneRegionScan      *Gene Region Scan*

---

### Description

The top-level wrapper function that outputs as much data as possible, concerning one or a few genes. Refer to the functions [plotCoexpression](#) and [plotOnGene](#) for further explanation of each part of the plot.

### Usage

```
geneRegionScan(object, gene, genomicData=NULL, probeData=NULL, label=NULL, g
```

### Arguments

object	A ProbeLevelSet object or a regular ExpressionSet object (in which case a probeData argument is required). See <a href="#">getLocalProbeIntensities</a> and related functions on how to create a ProbeLevelSet.
gene	A number of gene sequences as DNASTring, list of DNASTring objects, character-vectors or <a href="#">readFASTA</a> outputs.
genomicData	Optional. If only one gene is specified this can be of the same form as given in <a href="#">exonStructure</a> . If more than one gene is given, it must be a list, containing of one of these forms of the argument for each of the genes, in the same order.
probeData	Optional if a ProbeLevelSet is submitted as object argument. Otherwise, it must be a data frame with rownames corresponding to the featureNames of the ExpressionSet and a column named "sequence" with the probe sequences as character strings
label	An optional character string specifying a column name in the pData of the object. If this argument is given, the gene plot will be colour coded based on the different groups (factors) in the pData entry. If a summaryType other than 'dots' is selected the summarisation is done stratified by the different groups in the pData.
genename	Optional character string specifying a gene name to include in the plot. If not included and a FASTA sequence is given, it will default to the name in the FASTA sequence. Otherwise it will default to 'Unknown genename'.
summaryType	Character string specifying one of the following summary methods: 'median', 'mean', 'quartiles' or 'dots' (i.e. no summary). Specifies how all the sample values or all the samples values in a group if 'label' is given, should be summarised. Defaults to 'median'.
testType	Optional character string, defining a statistic procedure to identify especially interesting probes. Can be either 'linear model', 'students' or 'wilcoxons'. If given, a label must also be specified. In this case the <a href="#">plotStatistics</a> function will be called and probes that are significantly changed between the groups in label at the P-value set in cutoff (see cutoff argument) will be circled.
forcePValue	Logical. Is used if the testType argument is used. If TRUE all significantly changed probes have P-value given on the plot. If FALSE, only plots with less than 10 significant probes write P-values. Plots can become very cluttered with data if set to TRUE

verbose	TRUE or FALSE
cutoff	Integer specifying at what p-value probes should be circled when using the 'test-Type' variable. Defaults to 0.2. For cutoffs higher than 0.05, all probes with $P > 0.05$ will be circled in grey instead of black.
directions	A character vector of the matching-directions that should be scanned (which combinations of complementary and reverse). Defaults to "all" which is shorthand for all possible directions, but can take anything from: <code>c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense")</code>
correlationCutoff	A number between 0 and 1. The limit at which Pearson correlation (in absolute values) should not be plotted below. Defaults to 0.5
probeLevelInfo	The information about each probe to include in the plot. Should be a vector of one or more of the following elements: probeid, probesetid, sequence. Default is only probeid.
ylim	Label of Y-axis as in default plots

### Details

This function is a wrapper around [plotOnGene](#) and [plotCoexpression](#). The output of `plotOnGene` is included in the top half of the plot and the output of `plotCoexpression` will be included in the bottom half of the plot. Refer to each of these functions for more detailed help.

In general, this function gives an overview of how intensity values of individual probes on a microarray are in relation to an actual gene or set of genes in a region of the genome.

The function has only been tested with up to four genes at the same time. A plot with more genes would probably also be too complicated to interpret with this method. In addition, the alignment of the top and bottom plots also becomes somewhat difficult with more genes. This alignment is also the reason why the function can not export to any device.

See [getLocalProbeIntensities](#) for more info on how to obtain `ProbeLevelSets`.

### Value

No value, but plots the local expression levels of each probe found in the submitted sequence of the gene or genes as a function of its location along this sequence on the top half of a pdf-file. On the bottom half of the pdf-file it will plot the pairwise correlations between all probes found in the sequences. The pdf file will be named "report\\_\_" + title of `ExpressionSet` or `ProbeLevelSet`

### Author(s)

Lasse Folkersen

### See Also

[plotCoexpression](#), [plotOnGene](#), [getLocalProbeIntensities](#)

### Examples

```
data(exampleProbeLevelSet)

#simple:
geneRegionScan(exampleProbeLevelSet, mrna)
```

```
#more complicated - note that we slice the mrna to simulate comparing two different isoforms
gene1<-DNASTring(mrna[[1]]$seq) [1:1000]
gene2<-DNASTring(mrna[[1]]$seq) [1500:3000]

geneRegionScan(exampleProbeLevelSet, list(gene1,gene2), genomicData=list(genomic,genomic)
  testType="linear model", forcePValue=TRUE, cutoff=0.1, directions="all", correlationCutoff=0.5,
  probeLevelInfo=c("probeid","sequence"))
```

---

genomic	<i>genomic sequence of gene in ProbeLevelSet</i>
---------	--

---

### Description

This is the DNA sequence for fibronectin 1 isoform 2 preproprotein, which is used in the exampleProbeLevelSet. It has been split up so each exon in the gene is described in one FASTA entry.

### Usage

```
data(exampleProbeLevelSet)
```

### Format

It has been read from FASTA format using the [readFASTA](#) function. The FASTA was downloaded from <http://genome.ucsc.edu>, specifying "One FASTA record per region" in the "Sequence Retrieval Region Options".

### Author(s)

Lasse Folkersen

---

getLocalMetaprobeIntensities	<i>Get Metaprobe Intensities locally</i>
------------------------------	--

---

### Description

Function that will create an expressionset from cel files.

### Usage

```
getLocalMetaprobeIntensities(celfilePath, analysis="rma", metaProbeSetsFile=NULL,
  pgfPath=NULL, clfPath=NULL, cdfPath=NULL, verbose=TRUE)
```

**Arguments**

<code>celfilePath</code>	The path to a folder that contains the cel files of interest.
<code>analysis</code>	The analysis string passed to Affymetrix Power Tools. "RMA" and "RMA-sketch" are recommended starting points. See APT documentation for complete list of possibilities.
<code>metaProbeSetsFile</code>	Path to a file containing meta probe set information. These can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> and has names like <code>HuEx\1\0\st\v2.r2.dt1.hg18.full.mps</code> . This choice also decides which subset of the meta probe sets that will be used: Core, Extended or Full.
<code>annotation</code>	Character string specifying which type of arrays is investigated.
<code>aptProbesetSummarizePath</code>	The path to the <code>apt-probeset-summarize</code> file from the Affymetrix Power Tools package (including the filename itself). You can try to leave it as NULL and see what happens. If you have specified the argument before it will be remembered.
<code>pgfPath</code>	The path to a <code>pgf</code> file for the exon array of interest. This argument is mutually exclusive with the <code>cdfPath</code> argument. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.
<code>clfPath</code>	The path to a <code>clf</code> file for the exon array of interest. This argument is mutually exclusive with the <code>cdfPath</code> argument. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.
<code>cdfPath</code>	The path to a <code>cdf</code> file for the array of interest. This argument is mutually exclusive with the <code>pgfPath</code> and <code>clfPath</code> arguments. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.
<code>verbose</code>	TRUE or FALSE.

**Details**

This function is a simple wrapper around Affymetrix Power Tools (APT). It is useful for importing meta probe set data from cel files to R environments. It will remember the location of annotation files, after the first use, which removes some of the typing otherwise included in using APT. This function has now been updated so that a windows edition of `apt-probeset-summarize.exe` from APT-1.12.0 is included in the installation package, so that pre-processing of cel files can be done with less setup. Linux users will still have to install APT for this function.

**Value**

An Expressionset with meta probe set values for all meta probes in the specified `metaProbeSetFile`.

**Author(s)**

Lasse Folkersen

**See Also**

[getLocalProbeIntensities](#), [plotOnGene](#)

**Examples**

```
## Not run:
#must correct paths and give cel files before this example will work
listOfProbesets<-c("10321_at")
celfilePath<-path_to_some_cel_files
aptProbesetSummarizePath<-"/apt/apt-cel-extract"
cdfPath<-"/hgu133plus2.cdf"
getLocalMetaprobeIntensities(celfilePath, annotation="hgu133plus2", aptProbesetSummarizeP

## End(Not run)
```

---

```
getLocalProbeIntensities
      Get Probe Intensities locally
```

---

**Description**

Function that will create a ProbeLevelSet from cel files.

**Usage**

```
getLocalProbeIntensities(listOfProbesets, celfilePath, annotation=NULL, aptC
cdfPath=NULL, verbose=TRUE)
```

**Arguments**

listOfProbesets	Either a character vector with the names of the probesets from which probes should be included in the ProbeLevelSet, or the path name of a file containing this
celfilePath	The path to a folder that contains the cel files of interest.
annotation	Character string specifying which type of arrays is investigated.
aptCelExtractPath	The path to the apt-cel-extract file from the Affymetrix Power Tools package (including the filename itself). You can try to leave it as NULL and see what happens. If the tool is in path, it will work anyway. If you have specified the argument before it will be remembered. If you are using an OS for which executables have been included in the package (win32 and linux64), it will use that.
pgfPath	The path to a pgf file for the exon array of interest. This argument is mutually exclusive with the cdfPath argument. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.

<code>clfPath</code>	The path to a <code>clf</code> file for the exon array of interest. This argument is mutually exclusive with the <code>cdfPath</code> argument. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as <code>NULL</code> next time.
<code>cdfPath</code>	The path to a <code>cdf</code> file for the array of interest. This argument is mutually exclusive with the <code>pgfPath</code> and <code>clfPath</code> arguments. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as <code>NULL</code> next time.
<code>verbose</code>	TRUE or FALSE.

### Details

This is the workhorse function for generating `ProbeLevelSets`. It has two main functions: 1) It extracts the probe level intensity, normalizes it to all probes in the data using quantiles normalization and transfers the results to the `exprs` part of a `ProbeLevelSet`. The extraction and normalization parts are done by a call to the Affymetrix Power Tools (APT) function `apt-cel-extract`. The analysis switch for this call is `'-a quant-norm,pm-only'` and the documentation for APT can be used for further reference. 2) It extracts the probe sequences of all probes of interest. This is done using the `[arrayname]probe` packages for the 3'IVT type arrays for which they are available. For the exon type arrays, for which this is not available it is done by direct parsing of the `pgf` files using the `readPgf` function of the `affxparser` package. The results of this is saved in the `featureData` of the `ProbeLevelSet`

### Value

A `ProbeLevelSet` with probe intensity values for all probes in the specified probesets. The `ProbeLevelSet` inherits the `ExpressionSet`, but in addition it has the sequence of each probe stored in the `featureData` of the set.

### Author(s)

Lasse Folkersen

### See Also

[getServerProbeIntensities](#), [plotOnGene](#)

### Examples

```
## Not run:
#must correct paths and give cel files before this example will work
listOfProbesets<-c("10321_at")
celfilePath<-path_to_some_cel_files
aptCelExtractPath<-"~/apt/apt-cel-extract"
cdfPath<-"~/hgu133plus2.cdf"
getLocalProbeIntensities(listOfProbesets, celfilePath, annotation="hgu133plus2", aptCelEx

## End(Not run)
```



---

`getMetaprobeseSetsFromRegionOfInterest`*Get Meta Probe Set IDs From Region Of Interest*

---

**Description**

Function that return the meta probe set ids located within a given region of the genome.

**Usage**

```
getMetaprobeseSetsFromRegionOfInterest(annotation, chromosome, start, end, pythonP
```

**Arguments**

<code>annotation</code>	A character string giving the type of array for which probesets are needed. This is used to save the location of the transcriptClustersFile.
<code>chromosome</code>	The chromosome of interest. Should be given as a character string of the type "Chr1", "Chr2", "ChrY".
<code>start</code>	A character string with the start location of interest in the chromosome.
<code>end</code>	A character string with the end location of interest in the chromosome.
<code>pythonPath</code>	Optional character string with the path for Python software. This is only needed for exon arrays. If Python is in path this will be recognised automatically. Python can be downloaded from <a href="http://www.python.org">http://www.python.org</a> .
<code>transcriptClustersFile</code>	The location of a transcript cluster file such as HuEx-1\0-st-v2.na26.hg18.transcript.csv. These can be downloaded from <a href="http://www.affymetrix.com">http://www.affymetrix.com</a> .

**Details**

Since meta probe sets are only found in exon arrays, this function does not work with 3' IVT array files. It parses the location files from the <http://www.affymetrix.com> website using a python script. Admittedly this is not optional from an R-only point-of-view, but it works and its fast. The function will be updated when more R-centric ways of parsing exon array annotation data is available.

Alternatively this data can just as well be retrieved from the web, but in some cases this function is faster an easier.

**Value**

A list of all probesets found in the given range on the given chromosome.

**Author(s)**

Lasse Folkersen

**See Also**

[getLocalProbeIntensities](#), [getProbesetsFromRegionOfInterest](#)

**Examples**

```
## Not run:
#must supply transcriptClustersFile for this to work
metaprobesets<-getMetaprobesetsFromRegionOfInterest("notusedhere", chromosome=2, start="2

## End (Not run)
```

---

```
getProbeLevelAnnotationForExonArrays
Get ProbeLevel Annotation for Exon Arrays
```

---

**Description**

Internal function that will return exon probe sequence and probe id for all probes in a given list of probe sets.

**Usage**

```
getProbeLevelAnnotationForExonArrays(vectorOfProbesets, pgfPath)
```

**Arguments**

vectorOfProbesets	A character string with probeset IDs.
pgfPath	The path of a pgf file for the exon array type of interest. Can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> .

**Details**

This function makes a call to readPgf in the affxparser package to get the sequence information. The readPgf will then load the entire pgf file and that might be quite memory intensive. However it is not possible to extract the indices of the probeset names without doing this. The function is primarily intended to be called by [getLocalProbeIntensities](#).

The call to [readPgf](#) sometimes gives a is.na() warning. The reason for this is not known, but it does not seem to affect performance.

**Value**

A dataframe with a row for each probe in the submitted probeset. The columns with the names "probeset\\_name" and "sequence" contains this.

**Author(s)**

Lasse Folkersen

**See Also**

[readPgf](#), [getLocalProbeIntensities](#), [plotOnGene](#)

**Examples**

```
## Not run:
#must supply pgf file for this to work
getProbeLevelAnnotationForExonArrays("43254543", pgfPath=~ / somewhere / some.pgf")

## End(Not run)
```

---

```
getProbesetsFromMetaprobeset
      Get Probeset IDs From metaprobeset IDs
```

---

**Description**

Function that return the probesets mapping to a given set of metaprobesets.

**Usage**

```
getProbesetsFromMetaprobeset(annotation, metaprobesets, pythonPath=NULL, mps
```

**Arguments**

annotation	A character string giving the type of array for which probesets are needed. Will be used to load the .db file from bioconductor. Optional if mps to ps and transcript cluster file is given.
metaprobesets	A vector of characters giving the metaprobeset IDs for which to find the probe set IDs.
pythonPath	Optional character string with the path for Python software. This is only needed for exon arrays. If Python is in path this will be recognised automatically. Python can be downloaded from <a href="http://www.python.org">http://www.python.org</a> .
mpsToPsFile	The location of a transcript cluster file such as HuEx-1\0-st-v2.r2.dt1.hg18.full.mps. These can be downloaded from <a href="http://www.affymetrix.com">http://www.affymetrix.com</a> . Best to use the "full" type file.

**Details**

This function will parse the relevant library files from the <http://www.affymetrix.com> website using a python script. Admittedly this is not optional from an R-only point-of-view, but it works and its fast. The function will be updated when more R-centric ways of parsing exon array annotation data is available.

Alternatively this data can just as well be retrieved from the web, but in some cases this function is faster an easier.

**Value**

A list of all probesets found in the given metaprobesets.

**Author(s)**

Lasse Folkersen

**See Also**

[getLocalProbeIntensities](#), [getProbesetsFromRegionOfInterest](#), [getMetaprobesetsFromRegionOfInterest](#)

**Examples**

```
## Not run:
#must supply mpsToPsFile and transcriptClustersFile for this to work
probesets<-getProbesetsFromMetaprobeset("notusedhere", c("3218528","2423669"), transcriptClustersFile, mpsToPsFile)
## End(Not run)
```

---

```
getProbesetsFromRegionOfInterest
Get Probeset IDs From Region Of Interest
```

---

**Description**

Function that return the probesets located within a given region of the genome.

**Usage**

```
getProbesetsFromRegionOfInterest(annotation, chromosome, start, end, pythonPath, transcriptClustersFile, mpsToPsFile)
```

**Arguments**

annotation	A character string giving the type of array for which probesets are needed. Will be used to load the .db file from bioconductor. Optional if mps to ps and transcript cluster file is given.
chromosome	The chromosome of interest. Should be given as a character string of the type "Chr1", "Chr2", "ChrY".
start	A character string with the start location of interest in the chromosome.
end	A character string with the end location of interest in the chromosome.
pythonPath	Optional character string with the path for Python software. This is only needed for exon arrays. If Python is in path this will be recognised automatically. Python can be downloaded from <a href="http://www.python.org">http://www.python.org</a> .
transcriptClustersFile	The location of a transcript cluster file such as HuEx-1\0-st-v2.na26.hg18.transcript.csv. These can be downloaded from <a href="http://www.affymetrix.com">http://www.affymetrix.com</a> .
mpsToPsFile	The location of a transcript cluster file such as HuEx-1\0-st-v2.r2.dt1.hg18.full.mps. These can be downloaded from <a href="http://www.affymetrix.com">http://www.affymetrix.com</a> . Best to use the "full" type file.

**Details**

While working with 3'IVT type affymetrix arrays, for which .db files exist within the bioconductor environment, this function works in a pretty simple way. However if exon arrays are used, it will change to parsing the relevant library files from the <http://www.affymetrix.com> website using a python script. Admittedly this is not optional from an R-only point-of-view, but it works and its fast. The function will be updated when more R-centric ways of parsing exon array annotation data is available.

Alternatively this data can just as well be retrieved from the web, but in some cases this function is faster an easier.

**Value**

A list of all probesets found in the given range on the given chromosome.

**Author(s)**

Lasse Folkersen

**See Also**

[getLocalProbeIntensities](#), [getMetaprobesetsFromRegionOfInterest](#)

**Examples**

```
## Not run:
#must supply mpsToPsFile and transcriptClustersFile for this to work
probesets<-getProbesetsFromRegionOfInterest("notusedhere", chromosome=2, start="215889955")
## End (Not run)
```

---

getSequence	<i>Get Sequence from a ProbeLevelSet</i>
-------------	--

---

**Description**

Function to retrieve the sequences of feature in a ProbeLevelSet.

**Usage**

```
getSequence(object, id)
```

**Arguments**

object	A ProbeLevelSet object
id	Optional character vector with the featureNames of the sequences of interest

**Value**

A character vector with the sequences of all probes in the ProbeLevelSet. The names of the vector are set to match the sequences.

**Author(s)**

Diego Diez

**See Also**[ProbeLevelSet](#)**Examples**

```
data(exampleProbeLevelSet)
getSequence(exampleProbeLevelSet)
```

---

```
getServerProbeIntensities
    Get Probe Intensities from a server
```

---

**Description**

Wrapper around [getLocalProbeIntensities](#) that is designed to be run easily on remote computers.

**Usage**

```
getServerProbeIntensities(listOfProbesets, celfilePath, annotation=NULL, apt
```

**Arguments**

<code>listOfProbesets</code>	Either a character vector with the names of the probesets from which probes should be included in the ProbeLevelSet, or the path name of a file containing this
<code>celfilePath</code>	The path to a folder that contains the cel files of interest. If serveraddress is different from "localhost", this should be the path on the remote computer
<code>annotation</code>	Character string specifying which type of arrays is investigated. If a pgf file and clf file is specified this is optional.
<code>aptCelExtractPath</code>	The path to the apt-cel-extract file from the Affymetrix Power Tools package (including the filename itself). You can try to leave it as NULL and see what happens. If the tool is in path, it will work anyway. If you have specified the argument before it will be remembered. If you are using an OS for which executables have been included in the package (win32 and linux64), it will default to using that.
<code>pgfPath</code>	The path to a pgf file for the exon array of interest. This argument is mutually exclusive with the cdfPath argument. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.

clfPath	The path to a clf file for the exon array of interest. This argument is mutually exclusive with the cdfPath argument. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.
cdfPath	The path to a cdf file for the array of interest. This argument is mutually exclusive with the pgfPath and clfPath arguments. These files can be downloaded from <a href="http://www.affymetrix.com">www.affymetrix.com</a> for the array of interest. Once given for a particular annotation, the location is saved for future use and can be given as NULL next time.
serveraddress	Character string with the IP adress to a remote server. Defaults to "localhost", in which case the algorithm is run locally.
username	The username for the remote server. Optional if serveraddress is "localhost".
password	The password for the remote server. Optional if serveraddress is "localhost".
plinkPath	The path to the plink program. Can be found at <a href="http://www.chiark.greenend.org.uk/~sgtatham/putty/">http://www.chiark.greenend.org.uk/~sgtatham/putty/</a> Used to transfer commands to the remote server. Optional if serveraddress is "localhost".
pscpPath	The path to the pscp program. Can be found at <a href="http://www.chiark.greenend.org.uk/~sgtatham/putty/">http://www.chiark.greenend.org.uk/~sgtatham/putty/</a> Used to transfer commands to the remote server. Optional if serveraddress is "localhost".
verbose	TRUE or FALSE.

### Details

This function is a wrapper around [getLocalProbeIntensities](#). The main function of the getServerProbeIntensities function is to save all the data needed to start a getLocalProbeIntensities run, send it to a remote server, start the run, and return the data. This is useful if you have access to a fast server and want to work with large datasets of exon arrays.

### Value

A ProbeLevelSet with probe quantiles normalized intensity values for all probes in the specified probesets. The ProbeLevelSet inherits the ExpressionSet, but in addition it has the sequence of each probe stored in the featureData of the set.

### Author(s)

Lasse Folkersen

### See Also

[getLocalProbeIntensities](#), [plotOnGene](#)

### Examples

```
## Not run:
#must correct paths, username and password before this example will work
listOfProbesets<-c("10321_at")
celfilePath<-path_to_some_cel_files #remote
aptCelExtractPath<- "~/apt/apt-cel-extract" #remote
cdfPath<- "~/hgu133plus2.cdf" #remote
```

```

username<-"user1"
password<-"ZaphodBeeblebrox"
plinkPath<-"~/plink" #local
pscpPath<-"~/pscp" #local
getServerProbeIntensities(listOfProbesets, celfilePath, annotation="hgu133plus2", aptCelE
username=username, password=password, plinkPath=plinkPath, pscpPath=pscpPath)

## End(Not run)

```

---

mrna	<i>mRNA sequence of gene in ProbeLevelSet</i>
------	---

---

### Description

This is the mRNA sequence for fibronectin 1 isoform 2 preproprotein, which is used in the exampleProbeLevelSet.

### Usage

```
data(exampleProbeLevelSet)
```

### Format

It has been read from FASTA format using the [readFASTA](#) function.

### Author(s)

Lasse Folkersen

---

plotCoexpression	<i>Plot Coexpression of probes in a ProbeLevelSet</i>
------------------	---

---

### Description

Function that will investigate all possible pairings in a set of probes, calculate the Pearson correlation coefficient and plot them in a meaningful way

### Usage

```
plotCoexpression(object, gene, probeData=NULL, verbose=TRUE, directions="all",
probeLevelInfo=c("probeid"))
```



**Arguments**

object	A ProbeLevelSet object or a regular ExpressionSet object (in which case a probeData argument is required). See <a href="#">getLocalProbeIntensities</a> and related functions on how to create a ProbeLevelSet.
gene	A number of gene sequences as DNAstring, vectors of DNAStrings, character-vectors or <a href="#">readFASTA</a> outputs.
probeData	Optional if a ProbeLevelSet is submitted as object argument. Otherwise it must be a data frame with rownames corresponding to the featureNames of the ExpressionSet and a column named "sequence" with the probe sequences as character strings
verbose	TRUE or FALSE
directions	A character vector of the matching-directions that should be scanned (which combinations of complementary and reverse). Defaults to "all" which is shorthand for all possible directions, but can take anything from: c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense")
correlationCutoff	A number between 0 and 1. The limit at which Pearson correlation (in absolute values) should not be plotted below. Defaults to 0.5
probeLevelInfo	The information about each probe to include in the plot. Should be a vector of one or more of the following elements: probeid, probesetid, sequence. Default is only probeid.

**Details**

This function takes a ProbeLevelSet or an ExpressionSet + probeData and the sequence of a gene. It then calculates pairwise Pearson correlation coefficients between all possible combinations of probes. Then it assigns each probe to a location along the length of the gene and plots a relational graph showing which probes has high correlation coefficients. The correlation coefficients are sorted by absolute values meaning that it will also include the negative correlations.

**Value**

No value, but plots a hapmap style plot of correlation values between all probes

**Author(s)**

Lasse Folkersen

**See Also**

[geneRegionScan](#), [plotOnGene](#)

**Examples**

```
data(exampleProbeLevelSet)
plotCoexpression(exampleProbeLevelSet, mrna, correlationCutoff=0.7, probeLevelInfo=c
```

---

plotOnGene

*Plot probe level data on a gene*


---

### Description

Function that will investigate the probe level intensity of probes as a function of their location in a gene.

### Usage

```
plotOnGene(object, gene, probeData=NULL, label=NULL, genename=NULL, summaryType=NULL,
interval=NULL, ylim=NULL, testType=NULL, forcePValue=FALSE, verbose=TRUE, cutoff=NULL)
```

### Arguments

object	A ProbeLevelSet object or a regular ExpressionSet object (in which case a probeData argument is required). See <a href="#">getLocalProbeIntensities</a> and related functions on how to create a ProbeLevelSet.
gene	A number of gene sequences as DNASTring, vectors of DNASTrings, character-vectors or <a href="#">readFASTA</a> outputs.
probeData	Optional if a ProbeLevelSet is submitted as object argument. Otherwise, it must be a data frame with rownames corresponding to the featureNames of the ExpressionSet and a column named "sequence" with the probe sequences as character strings
label	An optional character string specifying a column name in the pData of the object. If this argument is given, the gene plot will be colour coded based on the different groups (factors) in the pData entry. If a summaryType other than 'dots' is selected the summarisation is done stratified by the different groups in the pData. It can be a numeric or integer entry, but it will be coerced to factors.
genename	Optional character string specifying a gene name to include in the plot. If not included and a FASTA sequence is given, it will default to the name in the FASTA sequence. Otherwise, it will default to 'Unknown genename'.
summaryType	Character string specifying one of the following summary methods: 'median', 'mean', 'quartiles' or 'dots' (i.e. no summary). Specifies how all the sample values or all the samples values in a group if 'label' is given, should be summarised. Defaults to 'median'.
interval	Optional vector of two integers of bp positions. If given, the plot will only include the sequence from gene in the given interval. The x-axis annotation is preserved from original, so this is useful for zooming on specific regions.
ylim	Optional two integers. If given, this value will be the minimal and maximal value on the y-axis. This is useful if a few outlier probes have very high intensity values, as the default is to set the ylim from the maximal intensity value.
testType	Optional character string, defining a statistic procedure to identify especially interesting probes. Can be either 'linear model', 'students' or 'wilcoxon'. If given, a label must also be specified. In this case the <a href="#">plotStatistics</a> function will be called and probes that are significantly changed between the groups in label at the P-value set in cutoff (see cutoff argument) will be circled.

<code>forcePValue</code>	Logical. Is used if the <code>testType</code> argument is used. If TRUE all significantly changed probes have P-value given on the plot. If FALSE, only plots with less than 10 significant probes write P-values. Plots can become very cluttered with data if set to TRUE
<code>verbose</code>	TRUE or FALSE
<code>cutoff</code>	Integer specifying at what p-value probes should be circled when using the 'test-Type' variable. Defaults to 0.2. For cutoffs higher than 0.05, all probes with $P > 0.05$ will be circled in grey instead of black.
<code>directions</code>	A character vector of the matching-directions that should be scanned (which combinations of complementary and reverse). Defaults to "all" which is shorthand for all possible directions, but can take anything from: <code>c("matchForwardSense", "matchForwardAntisense", "matchReverseSense", "matchReverseAntisense")</code>
<code>ylab</code>	Label of Y-axis as in default plots

## Details

At the very least, this function takes a `ProbeLevelSet` or an `ExpressionSet` + `probeData` and the sequence of a gene. It then compares the probe sequences given in the `ProbeLevelSet` or the `probeData` variable with the sequence of the gene given. Any probes with sequences found in the gene will be plotted, with their intensity level on the y-axis and their location in the gene on the x-axis. If no further arguments are given this gives a view of relative expression levels along the length of the gene, and can be used to investigate which exons are actively transcribed in the sample and which are not. An important argument that can be used for further investigation is the 'label' argument which specifies a column in the `pData` of the `ExpressionSet`. In this case the plots will be stratified by the factors specified in this column (so giving labels with numerical or Date class data will not work). This can be very useful when investigating how different sample conditions affect various regions of a gene. A transcript isoform that is relatively upregulated in a diseased state will for example not be discovered if a `probeset` or `metaprobeset` covering the entire gene is used to summarize the data, since the average expression intensity for the gene will remain constant. Using the `plotOnGene` function, however, and specifying a case / control label will reveal tendencies for probes at certain exon locations to have relation to this label. The `testType` argument further supports this functionality by providing statistical testing and highlighting of probes that correlate significantly to the given label. In the case / control example, a student's t-test would highlight all probes that matched with the exons of the gene that was only found in the disease-specific transcript isoform. When interpreting the data it is suggested that specific attention is paid to the pattern of probes in the same exon. A single probe with a P-value  $< 0.05$  might be a false positive caused by chance or by cross hybridization of the probe sequence to something else. A range of probes in the same exon that all show P-values below or close to 0.05, however, is much more likely to be an actual case of a transcript isoform having this particular exon or exons being regulated between the groups in the label. Exon structure can be easily plotted on the graph using the `exonStructure` function.

A special case is the search for SNPs which have effect on expression levels or variable splicing. The `testType` argument 'linear model' is designed for this. The linear model calls the internal function `doProbeLinear` which assign each of the levels in the 'label' column of the `pdata` a value between 1 and the number of levels, in the order in which they are sorted. For genotypes given as "AA", "AB", "BB" character strings this will give "AA" = 1, "AB" = 2 and "BB" = 3. The `doProbeLinear` then calculates a linear model between the intensity values and these numbers, and returns the P-value. In this case, low P-values can be interpreted as a case where the heterozygote samples have intermediary expression levels between the two homozygotes. This is the case that can be expected to be seen if the nucleotide type of SNP does in fact have any effect on the mRNA concentration levels in the sample.

**Value**

No value, but plots the local expression levels relations of each probe found in the submitted gene sequence as a function of its location along this sequence. Various statistics and summarizations on pdata can be employed, as specified in details.

**Author(s)**

Lasse Folkersen

**See Also**

[geneRegionScan](#), [plotCoexpression](#)

**Examples**

```
data(exampleProbeLevelSet)

plotOnGene(exampleProbeLevelSet, mrna, summaryType="dots", interval=c(500,1000))

plotOnGene(exampleProbeLevelSet, mrna, label="genotype3", testType="linear model")
exonStructure(mrna, genomic)
```

---

plotStatistics      *Plot Statistics*

---

**Description**

Internal function that will assist [plotOnGene](#) in identifying probes that are significantly changed in comparison with a given pData column.

**Usage**

```
plotStatistics(object, probeData, label, summaryType, testType, interval=NULL,
forcePValue=FALSE, verbose=TRUE, positionVector, ylim, xlim, cutoff=0.2)
```

**Arguments**

object	A ProbeLevelSet object or a regular ExpressionSet object (in which case a probeData argument is required).
probeData	Optional if a ProbeLevelSet is submitted as object argument. Otherwise it must be a data frame with rownames corresponding to the featureNames of the ExpressionSet and a column named "sequence" with the probe sequences as character strings
label	An optional character string specifying a column name in the pData of the object. If this argument is given, the gene plot will be colour coded based on the different groups (factors) in the pData entry. If a summaryType other than 'dots' is selected the summarisation is done stratified by the different groups in the pData.

summaryType	Character string specifying one of the following summary methods: 'median', 'mean', 'quartiles' or 'dots' (i.e. no summary). Specifies how all the sample values or all the samples values in a group if 'label' is given, should be summarised. Defaults to 'median'.
testType	Character string, defining a statistic procedure to identify especially interesting probes.
interval	Optional vector of two integers of bp positions. If given, the plot will only include the sequence from gene in the given interval. The x-axis annotation is preserved from original, so this is useful for zooming on specific regions.
forcePValue	Logical. Is used if the testType argument is used. If TRUE all significantly changed probes have P-value given on the plot. If FALSE, only plots with less than 10 probes significant write P-values. Plots can become very cluttered with data if set to TRUE
verbose	TRUE or FALSE
positionVector	A vector of integers and names specifying the position along the x-axis of each probe.
yylim	A vector of two integers. Specifies the decided ylim value passed into the plotting function.
xylim	A vector of two integers. Specifies the decided xlim value passed into the plotting function.
cutoff	Integer specifying at what p-value probes should be circled when using the 'test-Type' variable. Defaults to 0.2. For cutoffs higher than 0.05, all probes with P >0.05 will be circled in grey instead of black.

### Details

This function is not meant to be called by the user. It acts as an adapter between [plotOnGene](#) and either [doProbeLinear](#) or [doProbeTTest](#) depending on the testType variable.

### Value

No value, but decorates an existing plotOnGene plot with circles and p-values for all probes that are significant when investigating label with testType

### Author(s)

Lasse Folkersen

### See Also

[doProbeLinear](#), [doProbeTTest](#), [plotOnGene](#)

---

readGeneInput	<i>Standardize reading of gene inputs</i>
---------------	---

---

### Description

Internal function that will standardise the input of the many different form of sequences that can be used in Bioconductor.

### Usage

```
readGeneInput(gene, genename=NULL, verbose=TRUE)
```

### Arguments

gene	A number of gene sequences as DNASTring, list of DNASTring objects, character-vectors or <a href="#">readFASTA</a> outputs.
genename	Optional character string specifying a gene name to include in the plot. If not included and a FASTA sequence is given, it will default to the name in the FASTA sequence. Otherwise it will default to 'Unknown genename'.
verbose	TRUE or FALSE.

### Details

This function is not meant to be run directly by the user. It will take a number of genes either as a vector of characters, a path to a FASTA format file, as a vector of DNASTrings or as a readFASTA format. It will then output them in FASTA format for use with other functions. Optional variable genename forces a new name.

The primary objective of this function is to make the sequence input simpler for other functions.

### Value

A list of all sequences and their names, in exactly the same format as obtained with the [readFASTA](#) function of the Biostrings package.

### Author(s)

Lasse Folkersen

### See Also

[geneRegionScan](#), [plotOnGene](#)

### Examples

```
somegene<-"ATACCTTGTTAGGACCTGATGATAGATGCATAGTAATATCGTA"  
genename<-"My favourite gene"  
GeneRegionScan:::readGeneInput(somegene, genename=genename)
```

---

`translateSampleNames`*Translate sample names using translation file*

---

**Description**

Function that will change sample names in an ExpressionSet using a translation file.

**Usage**

```
translateSampleNames(object, translationFile, from, to)
```

**Arguments**

<code>object</code>	An ExpressionSet
<code>translationFile</code>	Character string with the path to a tab-separated text file with translations of names. Alternatively a data frame containing translation information.
<code>from</code>	Character string with the translationFile column name containing the values to translate from.
<code>to</code>	Character string with the translationFile column name containing the values to translate to.

**Details**

Function that can translate the sampleNames of an ExpressionSet when given translation information. The translationFile argument gives the translation between sampleNames as they are and the sampleNames as they should be. It can either be a character string with the path to a tab-separated text-file with headers or a directly a data frame with the necessary information. The variables 'from' and 'to' specify the column names that contains the translation information. They must be present in the translationFile and the entries in 'from' must be present in the sampleNames of the current ExpressionSet. Extra entries in the translationFile are omitted but samples in the ExpressionSet without samples in the translationFile will raise an error.

This package is particularly useful after running cel-files through the Affymetrix Power Tools (with [getLocalProbeIntensities](#) for example), since this program has a tendency to change any odd character in the filename to something else.

**Value**

The same ExpressionSet given as argument, but with sampleNames changed as specified in translationFile

**Author(s)**

Lasse Folkersen

**Examples**

```
data(exampleProbeLevelSet)

fromThese<-sampleNames(exampleProbeLevelSet)

toThese<-sub(".cel","", sampleNames(exampleProbeLevelSet))
toThese<-sub("X","", toThese)

translationFile<-cbind(fromThese, toThese)
translationFile<-as.data.frame(translationFile)

translateSampleNames(exampleProbeLevelSet, translationFile, from="fromThese", to="toThese")
```



# Index

## \*Topic **classes**

ProbeLevelSet-class, 1

## \*Topic **datasets**

exampleProbeLevelSet, 5

genomic, 13

mrna, 24

## \*Topic **documentation**

addSnpData, 1

checkForFileInPath, 2

doProbeLinear, 3

doProbeTTest, 4

excludeDoubleMatchingProbes,  
6

exonStructure, 7

findProbePositions, 8

findSequenceInGenome, 9

geneRegionScan, 11

getLocalMetaprobeIntensities,  
13

getLocalProbeIntensities, 15

getMetaprobesetsFromRegionOfInterest,  
17

getProbeLevelAnnotationForExonArrays,  
18

getProbesetsFromMetaprobeset,  
19

getProbesetsFromRegionOfInterest,  
20

getSequence, 21

getServerProbeIntensities, 22

plotCoexpression, 24

plotOnGene, 26

plotStatistics, 28

readGeneInput, 30

translateSampleNames, 31

## \*Topic **utilities**

addSnpData, 1

checkForFileInPath, 2

doProbeLinear, 3

doProbeTTest, 4

excludeDoubleMatchingProbes,  
6

exonStructure, 7

findProbePositions, 8

findSequenceInGenome, 9

geneRegionScan, 11

getLocalMetaprobeIntensities,  
13

getLocalProbeIntensities, 15

getMetaprobesetsFromRegionOfInterest,  
17

getProbeLevelAnnotationForExonArrays,  
18

getProbesetsFromMetaprobeset,  
19

getProbesetsFromRegionOfInterest,  
20

getSequence, 21

getServerProbeIntensities, 22

plotCoexpression, 24

plotOnGene, 26

plotStatistics, 28

readGeneInput, 30

translateSampleNames, 31

addSnpData, 1

addSnpData, ExpressionSet-method  
(addSnpData), 1

BSgenome, 7, 10

checkForFileInPath, 2

Comparison, 3

doProbeLinear, 3, 27, 29

doProbeTTest, 4, 29

exampleProbeLevelSet, 5

excludeDoubleMatchingProbes, 6, 7,  
10

excludeDoubleMatchingProbes, ProbeLevelSet-method  
(excludeDoubleMatchingProbes),

6

exonStructure, 7, 11, 27

findProbePositions, 8

findProbePositions, ExpressionSet-method  
(findProbePositions), 8

findSequenceInGenome, 7, 9

GeneRegionScan (*geneRegionScan*),  
11

geneRegionScan, 8, 9, 11, 25, 28, 30

geneRegionScan, ExpressionSet-method  
(*geneRegionScan*), 11

genomic, 13

getLocalMetaprobeIntensities, 13

getLocalProbeIntensities, 1, 2, 8,  
11, 12, 15, 15, 17, 18, 20–23, 25, 26,  
31

getMetaprobesetsFromRegionOfInterest,  
17, 20, 21

getProbeLevelAnnotationForExonArrays,  
18

getProbesetsFromMetaprobeset, 19

getProbesetsFromRegionOfInterest,  
17, 20, 20

getSequence, 21

getSequence, ProbeLevelSet-method  
(*getSequence*), 21

getServerProbeIntensities, 16, 22

matchPDict, 9, 10

mrna, 24

plotCoexpression, 9, 11, 12, 24, 28

plotCoexpression, ExpressionSet-method  
(*plotCoexpression*), 24

plotOnGene, 2–5, 8, 9, 11, 12, 15, 16, 18,  
23, 25, 26, 28–30

plotOnGene, ExpressionSet-method  
(*plotOnGene*), 26

plotStatistics, 3–5, 11, 26, 28

ProbeLevelSet, 5, 22

ProbeLevelSet  
(*ProbeLevelSet-class*), 1

ProbeLevelSet-class, 1

readFASTA, 7, 8, 11, 13, 24–26, 30

readGeneInput, 30

readPgf, 18

translateSampleNames, 31

translateSampleNames, ExpressionSet-method  
(*translateSampleNames*), 31