

Package ‘fCCAC’

October 16, 2018

Version 1.6.0

Date 2016-09-09

Type Package

Title functional Canonical Correlation Analysis to evaluate Covariance between nucleic acid sequencing datasets

Author Pedro Madrigal <dnaseiseq@gmail.com>

Description An application of functional canonical correlation analysis to assess covariance of nucleic acid sequencing datasets such as chromatin immunoprecipitation followed by deep sequencing (ChIP-seq).

Depends R (>= 3.3.0), S4Vectors, IRanges, GenomicRanges, grid

Maintainer Pedro Madrigal <pm12@sanger.ac.uk>

Imports fda, RColorBrewer, genomation, ggplot2, ComplexHeatmap, grDevices, stats, utils

Suggests RUnit, BiocGenerics, BiocStyle

License Artistic-2.0

LazyLoad yes

LazyData yes

biocViews Transcription, Genetics, Sequencing, Coverage

git_url <https://git.bioconductor.org/packages/fCCAC>

git_branch RELEASE_3_7

git_last_commit 25fe1de

git_last_commit_date 2018-04-30

Date/Publication 2018-10-15

R topics documented:

fCCAC-package	2
fccac	3
heatmapfCCAC	4
Index	6

fCCAC-package	<i>functional Canonical Correlation Analysis to evaluate Covariance between nucleic acid sequencing datasets</i>
---------------	--

Description

An application of functional canonical correlation analysis to assess covariance of nucleic acid sequencing datasets such as chromatin immunoprecipitation followed by deep sequencing (ChIP-seq).

Details

Package:	fCCAC
Type:	Package
Version:	0.99.0
Date:	2016-09-09
License:	Artistic-2.0
LazyLoad:	yes

Author(s)

Pedro Madrigal,
 Maintainer: Pedro Madrigal <dnaseiseq@gmail.com>

References

Madrigal P (2016) fCCAC: functional canonical correlation analysis to evaluate covariance between nucleic acid sequencing datasets. *Bioinformatics*: <http://doi.org/10.1093/bioinformatics/btw724>.

Examples

```
## hg19. chr21:40000000-48129895 H3K4me3 data from Bertero et al. (2015)
if (.Platform$OS.type == "unix") {

  owd <- setwd(tempdir())

  bigwig1 <- "chr21_H3K4me3_1.bw"
  bigwig2 <- "chr21_H3K4me3_2.bw"
  bigwig3 <- "chr21_H3K4me3_3.bw"
  peakFile <- "chr21_merged_ACT_K4.bed"
  labels <- c( "H3K4me3", "H3K4me3", "H3K4me3" )
  ti <- "H3K4me3 peaks"

  r1 <- system.file("extdata", bigwig1, package="fCCAC", mustWork = TRUE)
  r2 <- system.file("extdata", bigwig2, package="fCCAC", mustWork = TRUE)
  r3 <- system.file("extdata", bigwig3, package="fCCAC", mustWork = TRUE)
  r4 <- system.file("extdata", peakFile, package="fCCAC", mustWork = TRUE)
```

```

fc <- fccac(bar=NULL, main=ti, peaks=r4, bigwigs=c(r1,r2,r3), labels=labels, splines=15, nbins=100, ncan=15)

head(fc)

setwd(owd)
}

```

fccac

functional Canonical Correlation Analysis to evaluate Covariance between nucleic acid sequencing datasets

Description

functional Canonical Correlation Analysis to evaluate Covariance between nucleic acid sequencing datasets.

Usage

```

fccac(peaks, bigwigs, labels, splines=10, nbins=100, ncan=5 , tf=c(), main="",
bar=NULL, outFiles=FALSE )

```

Arguments

peaks	BED file. Column 1: chr, Column 2: start, Column 3: end (REQUIRED).
bigwigs	A vector of characters containing the path to bigwigs files. Replicates of the same samples should be entered consecutive one another (REQUIRED).
labels	IDs for each sample. Replicates should have the same label and be ordered (vector of characters, REQUIRED)
splines	Number of cubic B-splines used to smooth the data and to estimate the canonical variate weight functions (default: 15)
nbins	Integer value representing the number of bins that should be used for each window (default: 100)
ncan	Number of canonical components to report in the results. It cannot be higher than number of splines or the number of peaks (default: 15)
tf	Plot results involving only this TF or TF-replicate (character). Eg., "SOX2" or "SOX2_Rep1" (default: empty vector. plot all)
main	Title of the plot generated (default: no title)
bar	In the barplot, plot only first bar[1] and last bar[2] interactions after ranking by F-value (default: NULL, plots all the combinations).
outFiles	If TRUE, the function writes two files in the working directory, fCCAC.pdf and fCCAC.txt (tabulated text-file with results). (default: FALSE)

Details

Detailed information about the methodology can be found in Madrigal (2016).

Value

The function reports a dataframe with the following columns: pairwise samples, F value, k (order of the first canonical correlation), and value of the first canonical correlation.

Author(s)

Pedro Madrigal, <dnaseiseq@gmail.com>

References

Madrigal P (2016) fCCAC: functional canonical correlation analysis to evaluate covariance between nucleic acid sequencing datasets. *Bioinformatics*: <http://doi.org/10.1093/bioinformatics/btw724>.

See Also

[fCCAC-package](#)

Examples

```
## hg19. chr21:40000000-48129895 H3K4me3 data from Bertero et al. (2015)
if (.Platform$OS.type == "unix") {

  owd <- setwd(tempdir())

  bigwig1 <- "chr21_H3K4me3_1.bw"
  bigwig2 <- "chr21_H3K4me3_2.bw"
  bigwig3 <- "chr21_H3K4me3_3.bw"
  peakFile <- "chr21_merged_ACT_K4.bed"
  labels <- c( "H3K4me3", "H3K4me3", "H3K4me3" )

  r1 <- system.file("extdata", bigwig1, package="fCCAC", mustWork = TRUE)
  r2 <- system.file("extdata", bigwig2, package="fCCAC", mustWork = TRUE)
  r3 <- system.file("extdata", bigwig3, package="fCCAC", mustWork = TRUE)
  r4 <- system.file("extdata", peakFile, package="fCCAC", mustWork = TRUE)
  ti <- "H3K4me3 peaks"

  fc <- fccac(bar=NULL, main=ti, peaks=r4, bigwigs=c(r1,r2,r3), labels=labels, splines=15, nbins=100, ncan=15)

  head(fc)

  setwd(owd)
}
```

heatmapfCCAC

Heatmap of F values obtained by Canonical Correlation Analysis

Description

Heatmap of F values obtained by Canonical Correlation Analysis. This function can only be used if all pairwise comparisons were computed previously with the function 'fccac', i.e., using "tf=c()".

Usage

```
heatmapfCCAC(fc)
```

Arguments

fc Output of the function 'fccac'.

Value

Plots a Heatmap of F values using the package 'ComplexHeatmap'.

Author(s)

Pedro Madrigal, <dnaseiseq@gmail.com>

References

Madrigal P (2016) fCCAC: functional canonical correlation analysis to evaluate covariance between nucleic acid sequencing datasets. *Bioinformatics*: <http://doi.org/10.1093/bioinformatics/btw724>.

See Also

[fccac](#)

Examples

```
## hg19. chr21:40000000-48129895 H3K4me3 data from Bertero et al. (2015)
if (.Platform$OS.type == "unix") {

  owd <- setwd(tempdir())

  bigwig1 <- "chr21_H3K4me3_1.bw"
  bigwig2 <- "chr21_H3K4me3_2.bw"
  bigwig3 <- "chr21_H3K4me3_3.bw"
  peakFile <- "chr21_merged_ACT_K4.bed"
  labels <- c( "H3K4me3", "H3K4me3", "H3K4me3" )

  r1 <- system.file("extdata", bigwig1, package="fCCAC", mustWork = TRUE)
  r2 <- system.file("extdata", bigwig2, package="fCCAC", mustWork = TRUE)
  r3 <- system.file("extdata", bigwig3, package="fCCAC", mustWork = TRUE)
  r4 <- system.file("extdata", peakFile, package="fCCAC", mustWork = TRUE)
  ti <- "H3K4me3 peaks"

  fc <- fccac(bar=NULL, main=ti, peaks=r4, bigwigs=c(r1,r2,r3), labels=labels, splines=15, nbins=100, ncan=15)

  head(fc)

  heatmapfCCAC(fc)

  setwd(owd)

}
```

Index

fCCAC (fCCAC-package), [2](#)

fccac, [3](#), [5](#)

fCCAC-package, [2](#)

heatmapfCCAC, [4](#)